

Terpolymer Softener TSO-3210P

Terpolymer softener TSO-3210 is a medium to low viscosity diamino polydimethylsiloxane. Specially made for emulsion compound of textile softener and resin plasticizer. Low viscosity and easy to emulsify. Enhancing the washing fastness. Low contains D4、D5、D6, compliance to the REACH requirements.

Physical Properties

- Appearance : Transparent to translucent liquid type.
- Component : Diamino polydimethylsiloxane
- Solid Content: 30±1%
- PH value : 5.5~7.5
- Iconicity : Weak cation
- Stability : Stable and good compound ability
- Solubility : Easy soluble in water

Characteristics

- Low yellowing.
- Providing soft and silky hand feel and drapability.
- Increasing the resilience and crease recovery.
- Improved the tear strength and bursting strength of finished fabrics.
- It can be the lubricant for fleece and sanding process.

Application

- ⑩ General dosage is 2~3%
- ⑩ Please adjust the dosage according to the actual requirements.

Package

120Kg / Drum. The product should be stored at 5°C~30°C in original well-sealed container. Shelf life is 12 months.

LIMITED WARRANTY INFORMATION – PLEASE READ BEFORE ANY APPLICATION:

- The data presented in this brochure are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt.
- We reserve the right to alter product constants within the scope of technical progress or new developments.
- The recommendations made in this brochure should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used.
- The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights or patents and, if necessary, clarifying the position.
- Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.
- We disclaim any responsibility for any dispute regarding product quality between agent and end user.
- Our sole warranty is that our products will meet the sales specifications in effect at the time of shipment.