

Anti-static agent ASA-866

ASA-866 is an anti-static auxiliary with long-term effect. ASA-866 can provide excellent anti-static effects even in low humidity environments.

Physical Properties

- Appearance : Milky white opaque liquid
- Composition : Zwitterion surfactant
- Active ingredient : 11±1%
- PH value : 6~7
- Iconicity : Zwitterion
- Solubility : Soluble in water 、 acetone 、 ethyl alcohol 、 and other low molecular polar solvent.

Characteristics

- ASA-866 can be applied on PP/PE/PS/EPS/EPE/PVC/PET/Rubber/Silicon/PU made products.
- ASA-866 is suitable for fabric surface anti-static treatment.
- ASA-866 is nonmetal and no halogen ionic, it can be used for textile, fibers and any polymer made products.
- ASA-866 is odor-free, and with good thermal resistance.
- ASA-866 can improve the anti-static performance. The sheet resistance can be less than 107Ω/sq.

Application

The general dosage of ASA-866 is 50g/L. Please adjust the dosage according to the actual needs.

Package

120Kg drums.

LIMITED WARRANTY INFORMATION – PLEASE READ BEFORE ANY APPLICATION:

- The data presented in this brochure are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt.
- We reserve the right to alter product constants within the scope of technical progress or new developments.
- The recommendations made in this brochure should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used.
- The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights or patents and, if necessary, clarifying the position.
- Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.
- We disclaim any responsibility for any dispute regarding product quality between agent and end user.
- Our sole warranty is that our products will meet the sales specifications in effect at the time of shipment.