# **Durable antistatic agent ASA-900**

ASA-900 is a special soluble polymer. It is suitable for all kinds of fabric such as T/C, Polyester, nylon and so on. It can endow the fabric with excellent antistatic performance. Also it can prevent dyeing splash.

# [ Properties ]

1. Appearance: milk white to light yellow emulsion

2. Component: special polymer

3. Active content: 10±1%4. Ionic charge: cationic5. pH value : 5.0-7.0

6. Solubility: soluble in water

#### [ Characteristics ]

- 1. ASA-900 does not induce rusting.
- 2. ASA-900 does not influence the dyeing fastness.
- 3. ASA-900 has excellent antistatic performance.
- 4. ASA-900 is antistatic at low humidity.
- 5. ASA-900 is anti-washing and durable.

### Application 1

- 1. The sole usage is 20-50g/L and when used with water-absorption agent the usage is 1-3%
- 2. The compatibility must be tested when it is used with other additives.
- 3. The usage can be adjusted according to conditions.

## [ Storage]

Stored in closed containers at 5-35°C avoiding direct sunlight.

# [ Package]

120Kg per tub

#### LIMITED WARRANTY INFORMATION - PLEASE READ BEFORE ANY APPLICATION:

- The data presented in this brochure are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt.
- · We reserve the right to alter product constants within the scope of technical progress or new developments.
- The recommendations made in this brochure should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used.
- The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights or patents and, if necessary, clarifying the position.
- Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.
- $\bullet \ \ \text{We disclaim any responsibility for any dispute regarding product quality between agent and end user.}$
- Our sole warranty is that our products will meet the sales specifications in effect at the time of shipment.