

## Acid fluorescent dyes fixing agent YIMANFIX N-902N

Generally tannic acid fixing agent has great influence on fluorescent dyes color changing and reproducibility. Depending on this reason, we developed a nylon fixing agent YIMANFIX N-902 for fluorescent dyes. It can be used with acid fluorescent dyes for nylon fibers dyeing, and this agent has very small influence on fluorescent dyes color, even not changing colors, and good for color reproducibility after dyeing.

### 【 Properties 】

1. Appearance: transparent brown liquid
2. Ingredients: special polymer combining
3. Content: 40±1%
4. P H value: 2±1
5. Solubility: soluble in normal temp water
6. Iconicity: anion

### 【 Characteristics 】

1. YIMANFIX N-902N has very small influence on fluorescent dyes color and Light color fastness.
2. YIMANFIX N-902N has good fixing performance, upgrade wash fastness 1~1.5 grade.
3. YIMANFIX N-902N doesn't need to add acid, the dyeing bath very stable, without the generally fixing agent color spot problem.
4. YIMANFIX N-902N can promote seawater, light, and Perspiration color fastness.

### 【 Application 】

Suggested dosage: (customers can adjust it according to the test condition.)

YIMANFIX N-902N: 1-3% (o.w.f.). Bath ratio : 1 : 10-20, Temp: 80°C×20min, washing and drying.

### 【 Package 】

120KGS

---

#### LIMITED WARRANTY INFORMATION – PLEASE READ BEFORE ANY APPLICATION:

- The data presented in this brochure are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt.
- We reserve the right to alter product constants within the scope of technical progress or new developments.
- The recommendations made in this brochure should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used.
- The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights or patents and, if necessary, clarifying the position.
- Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.
- We disclaim any responsibility for any dispute regarding product quality between agent and end user.
- Our sole warranty is that our products will meet the sales specifications in effect at the time of shipment.